

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior revisions, and listings, of claims in the application.

**Listing of Claims:**

1. (Previously Presented) A culvert opening and cleaning apparatus for use with heavy machinery, comprising:

a telescoping arm member adapted to be mounted to an implement of a heavy machinery such that the telescoping arm is oriented vertically and where the telescoping arm member having an outer housing and an inner concentric arm that are telescopically slidable relative to each other;

a culvert cleaning tool substantially orthogonally mounted to the inner arm of the telescoping arm member and said culvert cleaning tool having a convex upward facing surface; and

a telescoping ram having at least one concentric cylinder and a piston that are telescopically slidable relative to each other and mounted in a substantially parallel side-by-side relationship relative to the telescoping arm, wherein a distal end of the piston is attached to the culvert cleaning tool for positing the culvert cleaning tool to be inserted in an opening of a culvert.

2. (Original) The culvert opening and cleaning apparatus for use with heavy machinery of claim 1, wherein the telescoping ram is operable to be powered by an auxiliary hydraulic of the heavy machinery.

3. (Previously Presented) The culvert opening and cleaning apparatus for use with heavy machinery of claim 2, wherein the culvert cleaning tool is a tapered shoe.

4. (Original) The culvert opening and cleaning apparatus of claim 1, where the telescoping arm member is adapted to be mounted to the implement with a mounting bracket attached to said telescoping arm and where said mounting bracket is adapted to be mounted to a grader blade implement.

5. (Previously Presented) A culvert opening and cleaning apparatus for use with heavy machinery, comprising:

a telescoping arm member adapted to be mounted to an implement of a heavy machinery such that the telescoping arm is oriented vertically and where the telescoping arm member comprises at least one interconnected outer housing cylinder and an inner concentric arm such that the outer housing and inner arm are telescopically slidable relative to each other; and

a culvert cleaning tool substantially orthogonally mounted to a distal end of the inner arm of the telescoping arm member and said culvert cleaning tool having a convex upward facing surface.

6. (Original) The culvert opening and cleaning apparatus for use with heavy machinery of claim 5, wherein the telescoping extension cylinder arm is operable to be powered by an auxiliary hydraulic of the heavy machinery.

7. (Original) The culvert opening and cleaning apparatus for use with heavy machinery of claim 6, wherein the telescoping arm member is adapted to be mounted to the implement with a mounting bracket attached to said telescoping arm and where said mounting bracket is adapted with a curved mounting surface to be mounted to a grader blade implement.

8. (Original) The culvert opening and cleaning apparatus for use with heavy machinery of claim 1, wherein the culvert cleaning tool is a tapered shoe.

9. (Cancelled)